

# AGROLUX



DEUTZ-FAHR  
AGROLUX  
65 - 75





| TECHNICAL DATA                                  | AGROLUX |                   |
|---|---------|-------------------|
|   | 65      | 75                |
| <b>ENGINE</b>                                   |         |                   |
| Emissions                                       | Tier3   | Tier3             |
| Manufacturer                                    | SDF     | SDF               |
| Cylinders/Capacity                              | No./cm3 | 3/3000            |
| Intake  | Turbo   | Turbo Intercooler |
| Max. homologated power (2000/25/EC) at 2200 rpm | kW/hp   | 45.6/62           |
| Max. torque at 1600 rpm                         | Nm      | 240               |
| Torque rise                                     | %       | 23                |
| Mechanical engine control                       | ●       | ●                 |
| Fuel tank capacity                              | litres  | 70                |
| <b>SHUTTLE</b>                                  |         |                   |
| Mechanical reverse shuttle                      | ●       | ●                 |
| <b>MECHANICAL GEARBOX</b>                       |         |                   |
| 4-speed   | ●       | ●                 |
| Number of speeds                                | n°      | 12 + 3            |
| Max. speed                                      | km/h    | 30                |
| <b>REAR PTO</b>                                 |         |                   |
| Mechanical engagement                           | ●       | ●                 |
| PTO 540   | ●       | ●                 |
| PTO 540/540ECO                                  | ○       | ○                 |
| <b>FRONT AND REAR AXLE</b>                      |         |                   |
| Four wheel drive mechanically engaged           | ●       | ●                 |
| Differential lock mechanically engaged          | ●       | ●                 |
| <b>BRAKES AND STEERING</b>                      |         |                   |
| Braking action on all 4 wheels                  | ●       | ●                 |
| Hydraulic trailer braking                       | ○       | ○                 |
| Hydrostatic steering with independent pump      | ●       | ●                 |
| Steering angle                                  | degrees | 55°               |
| <b>HITCH</b>                                    |         |                   |
| Mechanical rear hitch                           | ●       | ●                 |
| Rear hitch capacity                             | kg      | 2460              |
| <b>HYDRAULIC SYSTEM</b>                         |         |                   |
| Open-centre hydraulic system                    | ●       | ●                 |
| Pump output                                     | l/min   | 33                |
| Rear hydraulic auxiliary valves                 | No.     | 1 / 2             |
| <b>PLATFORM</b>                                 |         |                   |
| Lateral transmission levers                     | ●       | ●                 |
| Two-post folding ROPS                           | ●       | ●                 |
| Analogue instrumentation                        | ●       | ●                 |
| Driving seat mechanically adjustable            | ●       | ●                 |
| <b>DIMENSIONS AND WEIGHTS</b>                   |         |                   |
| Standard rear tyres                             |         | 420/85R28         |
| Max. length without rear linkage                | mm      | 3315              |
| Width (min./max.)                               | mm      | 1969 / 2269       |
| Max height at ROPS                              | mm      | 2470              |
| Ground clearance                                | mm      | 400               |
| Wheelbase (4WD- 2WD)                            | mm      | 1975 - 2037       |
| Rear track (min./max.)                          | mm      | 1402 / 1898       |
| Max. weight with ROPS (4WD - 2WD)               | kg      | 2800 - 2670       |
| Maximum permissible weight (4WD - 2WD)          | kg      | 4800 - 3800       |

Produced by Marketing/Communication Department - Code 308.8145.3.4-4 - 02/16

● STD ○ OPT

Contact your DEUTZ-FAHR dealer for more information or go to weblink [deutz-fahr.com/it-IT](http://deutz-fahr.com/it-IT).

DEUTZ-FAHR is a brand of SDF

