

AGROTRON K 410 • 420 • 610 • 430



EVOLVING AGRICULTURE.



TECHNICAL DATA

AGROTRON K 410 AGROTRON K 420 AGROTRON K 610 AGROTRON K 430

Version	4WD	4WD	4WD	4WD
	DEUTZ TIER III	DEUTZ TIER III	DEUTZ COMMON RAIL 2012 TIER III	DEUTZ COMMON RAIL 2012 TIER III
ENGINE				
Cylinders/Displacement	no./cc	4/4038	4/4038	6/6057
Aspiration			Turbo Intercooler	
Max. power	HP/KW	100/73	112/82	130/95
Homologated power at nominal engine speed (2000/25/CE)	HP/KW	100/73	112/82	127/93
Rated speed	rpm	2300		
Max. torque	Nm	378	398	475
Max. torque speed	rpm	1100-1700	1200-1800	1200-1800
Torque reserve	%	38	30	28
Cooling		liquid-oil		
Engine control		electronic		
Air cleaner		dry with safety cartridge		
Under-hood silencer		with exhaust at cab upright		
Fuel tank capacity	litres	180		
DIMENSIONS AND WEIGHTS (with rear tyres)		480/70 R 34	480/70 R 34	480/70 R 38
Max. length without link arms	mm	4140	4140	4370
Width min.- max.	mm	1880-2480	1880-2480	1880-2480
Max. height at cab	mm	2685	2685	2765
Ground clearance	mm	500	500	500
Wheelbase	mm	2419	2419	2647
Front track min.- max.	mm	1300-1800	1300-1800	1300-1800
Rear track min.- max.	mm	1400-2000	1400-2000	1400-2000
Minimum turning circle without brakes	mm	5455	5455	5850
Weight with safety frame	kg	4440	4440	4850

TRANSMISSION

Gearbox clutch	oil bath, hydrostatically operated
Gearbox with 4 synchronised gears, 3 Powershift ratios, 2 electrohydraulically engaged ranges (min. speed: 1.67 km/h)	24 FWD + 8 REV
Gearbox with 4 synchronised gears, 3 Powershift ratios, 2 electrohydraulically engaged ranges + creeper (min. speed: 0.33 km/h)	36FWD + 12 REV
Max. speed	50 Km/h restricted to 40 at rated or economy engine speed (1840 rpm) by electronic regulator
Hydraulic power shuttle	with electronically controlled double multi-disc oil bath clutch with control lever below steering wheel
Rear differential lock	electrohydraulically engaged
Lubrication	forced + transmission oil cooler

REAR PTO

Clutch	multi-disc, oil bath
Speed	540 540ECO 1000 1000ECO
Operation	synchronised PTO with independent drive shaft electrohydraulic with push-button control

FRONT PTO

Clutch	multi-disc, oil bath
Speed	1000
Operation	electrohydraulic, push-button control

BRAKES AND STEERING

Brakes	hydrostatic with rear discs in oil bath and DT coupling for hydraulic braking valve
Trailer braking	hydraulic or pneumatic braking system
Hydrostatic steering	independent pump, adjustable steering wheel
Steering angle	52°

FRONT AXLE

Type	conventional with automatically activated hydraulic suspension
Front wheel drive	electrohydraulically engaged
Front differential lock	multi-disc, oil bath
Front ballast	SBA/ASM: automatic control of front wheel drive and differentials
Front mudguards	ballast frame (330 kg) and 10 case type weights (40kg) steering

HYDRAULIC LIFT

rear lift	electronically controlled with Radar
Max. lifting capacity	kg 6200
Pump delivery	75
Electrohydraulic auxiliary control valves	no. ways 6
3 point linkage (link arms & top link)	automatic coupling with raised arm swing damping
Front lift	double acting cylinders maximum lifting capacity 3200 kg

DRIVING POSITION

Controls	ergonomic gear lever with buttons for powershift, range and clutch
Cab	original soundproofed (72 dbA) with platform suspension, high visibility roof, rear wiper, 8 work lights, telescopic rear-view mirrors as above with self-adjusting pneumatic suspension
Cab air conditioning	automatic air conditioner, drinks cooler, ventilation, heating and forced recirculation
Instrumentation	analogue with digital display
Driving seat	with pneumatic suspension and seat belt

HI-LINE VERSION

Automatic Powershift (APS)
Closed centre hydraulic system with 83 l/min variable displacement pump and load sensing function
4 electrohydraulic auxiliary control valves with flow control and delivery timing
Multi-functional armrest with integrated joystick
S.D.S.: programming and memorisation of repetitive actions
Performance monitor for productivity control
Automatic air conditioning system

The above specifications refer to the most complete level of equipment available. See the current price list and ask your local dealer for further information on standard and optional equipment.

*=SPEED ELECTRONICALLY RESTRICTED TO 40 KM/H FOR LEGAL PURPOSES
N.B.: SPEEDS IN REVERSE ARE SLIGHTLY HIGHER THAN THE CORRESPONDING FORWARD SPEEDS.

The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.
Cod.: 308.8175.3.4-2-09/10 - CFV

SAME DEUTZ-FAHR DEUTSCHLAND GmbH
Deutz-Fahr-Straße 1 _ D-89415 Lauingen _ Germany _ www.samedeutz-fahr.de

SAME DEUTZ-FAHR U.K. LTD.
Barby Lane, Barby, Nr Rugby _ CV23 8TD _ WARWICKSHIRE _ UK



EVOLVING AGRICULTURE.